



2' x 2' Flat Panel Compatible with Battery Back-Up

4000 lm | 100-277VAC | Model 54320142 | Part FPE-22-40-840-MV-D

- > Energy Saving 40 Watt Integrated LED
- > Cool White 4000K CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty
- > Compatible with Battery Back-Up



SPECIFICATIONS

Model	54320142
Part	FPE-22-40-840-MV-D
Description	2' X 2' Flat Panel, Compatible with Battery Back-Up
Input Voltage (VAC)	100-277
Wattage	40
Dimmability	0-10V
Average Rated Life ¹	50,000 hours
Typical Lumens ²	4000
CCT ³	4000k
Location Rating	UL Damp
CRI ⁴	≥80
Beam Angle	120°
Operating Temperature	Min -13°F (-25° C) Max 113°F (45° C)
Power Factor	>0.9
R9	4
DUV	0.0032
CBCP	1442
Operating Frequency (Hz)	50/60

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra

TO ORDER:

www.ETiSSL.com

Call: 1.855.ETi.SSLI

1.855.384.7754





2' x 2' Flat Panel Compatible with Battery Back-Up

4000 lms | 100-277VAC | Model 54320142 | Part FPE-22-40-840-MV-D

SHIPPING INFORMATION

Model	54320142
Part	FPE-22-40-840-MV-D
UPC	849489005249
Product Dimensions (L x W x H in.)	1' 11 47/64 x 1' 11 47/64 x 25/64
Product Dimensions (L x W x H cm.)	60.30 x 60.30 x 0.99
Product Weight (lbs.)	8.14
Inner Carton Quantity	2
Inner Carton Bar Code	30849489005240
Inner Carton Dimensions (L x W x H in.)	2' 39/64 x 2' 39/64 x 2 49/64
Inner Carton Dimensions (L x W x H cm.)	62.51 x 62.51 x 7.01
Inner Carton Weight (lbs)	17.4
Master Carton Quantity	4
Master Carton Bar Code	50849489005244
Master Carton Dimensions (L x W x H in.)	2' 11 3/64 x 2' 1 25/64 x 6 11/16
Master Carton Dimensions (L x W x H cm.)	64.01 x 64.49 x 16.99
Master Carton Weight (lbs)	37.04
Pallet Quantity	80

COMPATIBILITY

Dimmers: NA

Brand	MODEL NO.
Lutron	NFTV
Leviton	IPL710 DLZ
Leviton	IPL711 DL
Cooper	SF10P-W

Accessories

Category - Model NO.

ETi Battery Back-up - Model # 90600143

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256