



Traditional 1' x 4' LED Ceiling

3000 lm | 120VAC | Model 54644142 | Part CL-14-40-840-SV-D-H

- > Energy Saving 40 Watt Integrated LED
- > Uses 60% Less Energy than 100 Watt Fluorescent Equivalent
- > Cool White 4000? CCT
- > Lasts 45 years or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty
- > LED provided by Samsung as of 6/2018



SPECIFICATIONS

Model	54644142
Part	CL-14-40-840-SV-D-H
Description	Traditional 1' x 4' LED Ceiling Light
Input Voltage (VAC)	120
Wattage	40
Dimmability	Triac
Average Rated Life ¹	50,000 hours
Typical Lumens ²	3000
CCT ³	4000K
Location Rating	UL Damp
CRI ⁴	80
Beam Angle	120
Operating Temperature	Min -4°F (-20° C) Max 95°F (35° C)
Power Factor	>0.9
R9	49
DUV	-0.000629
CBCP	1060
Operating Frequency (Hz)	60

1 Hours lifetime with 70% lumen maintenance
 2 Thermally stable typical lumens (±10%)
 3 Thermally stable CCT (±10%)
 4 Color rendering index/Ra

ETI

LED lighting facts

Light Output (Lumens)	3000
Watts	40
Lumens per Watt (Efficacy)	75
Color Accuracy Color Rendering Index (CRI)	80
Light Color Correlated Color Temperature (CCT)	4000 (Bright White)

2700K 3000K 4000K 4500K 6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: 5BAM-X4YXBU (Revised 1/10/2017)
 Model Number: 546441##(##=41-50)
 Type: Luminaire - Linear

TO ORDER:
www.ETiSSL.com
 Call: 1.855.ETi.SSLI
 1.855.384.7754





Traditional 1' x 4' LED Ceiling

3000 lm | 120VAC | Model 54644142 | Part CL-14-40-840-SV-D-H

SHIPPING INFORMATION

Model	54644142
Part	CL-14-40-840-SV-D-H
UPC	836607009456
Product Dimensions (L x W x H in.)	4' 7/16 x 9 21/32 x 3 25/32
Product Dimensions (L x W x H cm.)	123.0 x 24.51 x 9.6
Product Weight (lbs.)	6.39
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	1
Master Carton Bar Code	836607009432
Master Carton Dimensions (L x W x H in.)	4' 5 7/16 x 1' 1 1/16 x 6.3
Master Carton Dimensions (L x W x H cm.)	135.7 x 32.2 x 16.0
Master Carton Weight (lbs)	9.04
Pallet Quantity	30

COMPATIBILITY

Dimmers:

Lutron	Leviton	Legrand	Cooper	Aspire
SCL-153PR-WH	81000-I	ADWR703HW4	SCL03P-A-K	9534DS-K
MACL-153M-WH	IPL06		DLC03P-LA	9573WS
MSCL-OP153M-WH	IPL06-10Z			
DV-603PG-AL				
LG-600H-WH				
GL-600H-DK				
TG-603PGH-WH				

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etissl.com/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256