

2FT Linear High Bay

18,000 lm | 120-277VAC | Model 50232162 | Part HB-171-850-MV-D

- > Energy Saving 171 Watt Integrated LED
- > Daylight 5000K CCT
- > Rated Life: 50,000 Hours
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty
- > Impact resistant tempered glass lenses



SPECIFICATIONS

Model	50232162
Part	HB-171-850-MV-D
Description	2FT Linear High Bay
Input Voltage (VAC)	120-277
Wattage	171
Dimmability	0-10V Dimmable
Average Rated Life¹	50,000 hours
Typical Lumens²	18,000
CCT³	5000K
Location Rating	UL Damp
CRI⁴	80
Beam Angle	86°
Operating Temperature	Min -40°F (-40° C), Max 113°F (45° C)
Power Factor	>0.9
R9	18
DUV	0.00133
CBCP	9190
Operating Frequency (Hz)	50/60

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra

TO ORDER:

www.ETiSSL.com

Call: 1.855.ETi.SSLI

1.855.384.7754





2FT Linear High Bay

18,000 lm | 120-277VAC | Model 50232162 | Part HB-171-850-MV-D

SHIPPING INFORMATION

Model	50232162
Part	HB-171-850-MV-D
UPC	849489009988
Product Dimensions (L x W x H in.)	2' 23/32" x 1' 19/32" x 3 5/8"
Product Dimensions (L x W x H cm.)	62.8 x 32.0 x 9.2
Product Weight (lbs.)	12.13
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	1
Master Carton Bar Code	50849489009983
Master Carton Dimensions (L x W x H in.)	2' 2 31/32"x 1' 2 29/64"x 5 11/32"
Master Carton Dimensions (L x W x H cm.)	68.5 x 36.7 x 13.6
Master Carton Weight (lbs)	14.3
Pallet Quantity	40

COMPATIBILITY

Dimmer Brand	Dimmer Model#
Lutron	DVTV-IV
Lutron	DVSTV-WH
Lutron	NFTV-WH
Lutron	NTSTV-DV-WH
Lutron	DVTV-WH
Leviton	IP710-DLZ

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256