

Nightlight

4" & 6" COLOR PREFERENCE® Downlight with Nightlight Trim

4" or 6"
Models!



○NightLIGHTR
Recessed Downlight

Integrated
Nightlight trim
emits warm
2000K glow



ETI ADVANTAGE



- ✓ TRIAC dimmable
- ✓ Direct insulation contact IC rated
- ✓ Meets NECA 410.16 requirements
- ✓ UL wet rating



COLOR PREFERENCE®

- ✓ Patented 5 CCT COLOR PREFERENCE® technology

Integrated Nightlight Trim Emits Warm 2000K Glow!

Technology

- Integrated 2000K nightlight can be turned on/off by toggling wall light switch!
- 5 CCT COLOR PREFERENCE® technology delivers total choice of CCT: 2700K, 3000K, 3500K, 4000K, or 5000K

Control

- Dimmable with TRIAC dimmer

Features & Specifications

- 120V
- 90CRI
- Temp rating -4°F - 104 °F
- UL wet rating
- IC rated for direct contact with insulation
- Meets NECA 410.16 requirements
- Certified airtight per ASTM E283-04
- L70 >50,000

*USA Patent 15/871,433, **Patent Pending

ETI SOLID STATE®
LIGHTING
INC.

North American Headquarters
720 Northgate Parkway
Wheeling, IL 60090

Customer Service
1-855-384-7754

Visit Us Online
www.ETISSL.com

Nightlight

4" & 6" COLOR PREFERENCE® Downlight with Nightlight Trim



WARM WHITE (2700K)
SOFT WHITE (3000K)
BRIGHT WHITE (3500K)
COOL WHITE (4000K)
DAYLIGHT (5000K)



COLOR PREFERENCE®

Selectable
5-CCT

- ✓ **4" COLOR PREFERENCE® w/ Nightlight 53808211**
DL-4-65-906-SV-D
- ✓ **6" COLOR PREFERENCE® w/ Nightlight 53807211**
DL-5-90-906-SV-D

PART NUMBER GUIDE

CATEGORY	SIZE	LUMENS	CRI/CCT	VOLTAGE	DIMMABILITY
DL			907	SV	D

PRODUCT/SKU DETAILS

GENERAL SPECIFICATIONS:

Voltage	120V	Frequency	50/60 Hz.	CRI	90
Power Factor	>.90	THD	< 20%	Rating	cULus Damp
Temperature	-4°F to +113°F	Rated Life	50,000 hrs.	Warranty	5 Year Limited

ORDERING GUIDE

Part #	Model #	Description	Replaces	LED Watts	Lumens	LPW	CCT	Product Dim.	CRI	Input Voltage	Case Pack
DL-4-625-907-SV-D	53805102	4" COLOR PREFERENCE® Downlight with Nightlight Trim - TRIAC Dimmable	65w Par	10.5w	625	60	27/30/35/40/5000K	4.92 X 3.05 in.	90	120V	4
DL-6-67-907-SV-D	53804102	6" COLOR PREFERENCE® Downlight with Nightlight Trim - TRIAC Dimmable	65w Par	11w	670	61	27/30/35/40/5000K	7.48 X 3.39 in.	90	120V	4

PACKAGING SPECIFICATIONS

Part #	Model #	UPC	UCC	Inner Carton Dimensions	Inner Carton Weight	Shipper/Master Carton Dimensions	Shipper/Master Carton Weight
DL-4-625-907-SV-D	53805102	849489004020	50849489004025	5.7 x 3.3 x 5.7 in.	0.8 lbs.	14.1 x 6.3 x 6.5 in.	3.9 lbs.
DL-6-67-907-SV-D	53804102	849489004037	50849489004032	7.9 x 3.6 x 7.9 in.	1.1 lbs.	15.2 x 8.5 x 8.7 in.	5.2 lbs.

COMPATIBLE DIMMERS

LUTRON: DVCL-153, CTCL-153P, TGCL-153P, MACL-153M, PD-6WCL, LECL-153, SCL-153P, NTCL-250, GT-150

LEVITON: 6674, 6672, IPL06-10Z, DSL06-1LZ, TSL06, RDL06

EATON: SAL06P2

COOPER: DLC03P, SUT7, TAL06P2