



# Reva 1' x 4' LED Ceiling

3000 lm | 120VAC | Model 54647142 | Part CL-14-40-840-SV-D-G

- > Energy Saving 40 Watt Integrated LED
- > Uses 60% Less Energy than 100 Watt Fluorescent Equivalent
- > Cool White 4000K CCT
- > Lasts 45 years or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



## SPECIFICATIONS

<b>Model</b>	54647142
<b>Part</b>	CL-14-40-840-SV-D-G
<b>Description</b>	Reva 1' x 4' LED Ceiling Light - Dimmable
<b>Input Voltage (VAC)</b>	120
<b>Wattage</b>	40
<b>Dimmability</b>	Triac
<b>Average Rated Life<sup>1</sup></b>	50,000 hours
<b>Typical Lumens<sup>2</sup></b>	3000
<b>CCT<sup>3</sup></b>	4000K
<b>Location Rating</b>	UL Damp
<b>CRI<sup>4</sup></b>	80
<b>Beam Angle</b>	120
<b>Operating Temperature</b>	Min -4°F (-20° C), Max 95°F (35° C)
<b>Power Factor</b>	>0.9
<b>R9</b>	47
<b>DUV</b>	-0.000676
<b>CBCP</b>	1872
<b>Operating Frequency (Hz)</b>	60

1 Hours lifetime with 70% lumen maintenance  
 2 Thermally stable typical lumens (±10%)  
 3 Thermally stable CCT (±10%)  
 4 Color rendering index/Ra

ETI

**LED lighting facts**  
A Program of the U.S. DOE

<b>Light Output (Lumens)</b>	<b>3000</b>
<b>Watts</b>	<b>40</b>
<b>Lumens per Watt (Efficacy)</b>	<b>75</b>
<b>Color Accuracy</b>	
Color Rendering Index (CRI)	<b>80</b>
<b>Light Color</b>	
Correlated Color Temperature (CCT) <b>4000 (Bright White)</b>	
Warm White	Bright White
Daylight	
2700K	3000K
4500K	6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: YN84-685214 (1/10/2017)  
 Model Number: 54647142(##=41-50)  
 Type: Luminaire - Linear

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
 Call: 1.855.ETi.SSLI  
 1.855.384.7754





# Reva 1' x 4' LED Ceiling

3000 lm | 120VAC | Model 54647142 | Part CL-14-40-840-SV-D-G

## SHIPPING INFORMATION

Model	54647142
Part	CL-14-40-840-SV-D-G
UPC	836607009418
Product Dimensions (L x W x H in.)	4' 1 1/64" x 10 15/64" x 3 15/16"
Product Dimensions (L x W x H cm.)	124.5 x 26.0 x 10.0
Product Weight (lbs.)	7.05
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	1
Master Carton Bar Code	836607009418
Master Carton Dimensions (L x W x H in.)	4' 5 7/64" x 1' 11/16" x 6 9/16"
Master Carton Dimensions (L x W x H cm.)	134.9 x 32.2 x 16.7
Master Carton Weight (lbs)	8.86
Pallet Quantity	30

## COMPATIBILITY

### Dimmers:

Lutron	Leviton	Legrand	Cooper	Aspire
SCL-153PR-WH	81000-I	ADWR703HW4	SCL03P-A-K	9534DS-K
MACL-153M-WH	IPL06		DLC03P-LA	9573WS
MSCL-OP153M-WH	IPL06-10Z			
DV-603PG-AL				
LG-600H-WH				
GL-600H-DK				
TG-603PGH-WH				

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.etissl.com/fcc15b](http://www.etissl.com/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

**ETi Solid State Lighting, Inc.**  
720 Corporate Woods Parkway  
Vernon Hills, IL 60061  
Phone: 855.384.7754  
Fax: 847.383.6256