

# Internal Motion Sensor

**90600145**

## SPECIFICATIONS




The 120/277V Internal Motion Sensor with advance controls is ideal for T24 regulated environments, as the motion sensor meets the strict lighting guidelines that address daylight and time delays, is easily controllable. Perfect for rooms where lights are often left on, such as an offices, or rooms where you need lighting turned on as you enter, like a supply closet. Comes with a 5 year warranty. Suitable for installations that operate between -4° F ~140° F.

Typical applications includes indoor warehouse, gymnasium, recreational space, retail, public spaces, schools, loading dock, garages and assembly lines and production facilities.

### KEY FEATURES & BENEFITS

- Operating Voltage: 120/277V
- Hold Time: 10s~30min
- Mounting Height: 19.7FT
- Protection Level: IP20
- Daylight Sensor: 5lux/10lux/30lux/50lux/Disable
- Hold Time: 10s/30s/90s/3min/20min/30min
- Rated load: 400W (inductive), 800W (resistive)
- Detection Angle: 150° (wall installation), 360° (ceiling installation)

### FIXTURE DIMENSIONS



SKU# 90600145  
Dimension A= 3.54"  
Dimension B= 1.44"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.etissl.us/fcc15b](http://www.etissl.us/fcc15b)

# Internal Motion Sensor

## 90600145

### SPECIFICATION DATA

Item Number	Description	Input Voltage (VAC)	Average Rated Life <sup>1</sup>	Typical Lumens <sup>2</sup>	CCT <sup>3</sup>	CRI <sup>4</sup>	Power Factor	R9	DUV	CBCP	Beam	Operating Frequency
90600145	Internal Motion Sensor	120/277	50,000 hours									50/60Hz
<sup>1</sup> Hours lifetime with 70% lumen maintenance												
<sup>2</sup> Thermally stable typical lumens												
<sup>3</sup> Thermally stable CCT												
<sup>4</sup> Color rendering index/Ra												

### SHIPPING INFORMATION

Item Number	Item UPC	Item Dimensions (L x W x H)	Item Weight (lbs)	Inner Pack Qty	Inner Carton Bar Code	Inner Carton Dimensions (L x W x H)	Inner Pack Weight (lbs)	Master Pack QTY	Master Carton Bar Code	Master Dimensions (L x x W)	Master Pack Weight (lbs)
90600145	849489 009759	3.54" x 1.44" x 1.00"		4	3084948 9009750	6.06" x 3.82" x 2.20"	0.9	60	5084948 9009754	19.13" x 12.05" x 4.53"	14.59

### COMPATIBLE LIST

Category	SKU#
Wrap Light	WR-4-40-840-MV-D WR-4-40-840-MV-D-EM WR-4-57-840-MV-D WR-2-20-840-MV-D
Vapor Tight	VT-4-34-840-MV VT-4-34-840-MV-EM VT-4-51-840-MV



The Americas Headquarters  
720 Corporate Woods Parkway  
Vernon Hills, IL 60061  
855-384-7754  
[www.etissl.com](http://www.etissl.com)