

5"/6" Recessed Retrofit Downlight

1300lm | 120VAC | Model 53179111 | Part DL-6-18-930-SV-D

- > Energy Saving 18 Watt Integrated LED
- > Uses 82% Less Energy than Equivalent 150 Watt Incandescent Bulb
- > Soft White 3000K CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty
- > IC Rated for Direct Contact with Insulation



SPECIFICATIONS

Model	53179111
Part	DL-6-18-930-SV-D
Description	5"/6" Recessed Retrofit Downlight Kit
Input Voltage (VAC)	120
Wattage	18
Dimmability	Triac
Average Rated Life¹	50,000 hours
Typical Lumens²	1300
CCT³	3000K
Location Rating	UL Wet
CRI⁴	90
Beam Angle	100
Operating Temperature	Min -4°F (-20° C), Max 113°F (45° C)
Power Factor	>0.9
R9	41
DUV	0.00135
CBCP	665
Operating Frequency (Hz)	60

- 1 Hours lifetime with 70% lumen maintenance
 2 Thermally stable typical lumens (±10%)
 3 Thermally stable CCT (±10%)
 4 Color rendering index/Ra

ETI

LED lighting facts[®]
A Program of the U.S. DOE

Light Output (Lumens)	1300
Watts	18
Lumens per Watt (Efficacy)	72.22
Color Accuracy Color Rendering Index (CRI)	
90	
Light Color Correlated Color Temperature (CCT)	
3000 (Bright White)	
Warm White 2700K	Bright White 3000K
4500K	Daylight 6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: 5BAM-H3GGUR (Revised 3/25/2016)
 Model Number: 531791XX(XX=11-30)
 Type: Retrofit Kit - Downlight

TO ORDER:
www.ETiSSL.com
 Call: 1.855.ETi.SSLI
 1.855.384.7754





5 1/8" Recessed Retrofit Downlight

1300 lm | 120VAC | Model 53179111 | Part DL-6-18-930-SV-D

SHIPPING INFORMATION

Model	53179111
Part	DL-6-18-930-SV-D
UPC	849489003160
Product Dimensions (W x H in.)	7 31/64 x 3 17/64
Product Dimensions (W x H cm.)	19 x 8.31
Product Weight (lbs.)	0.79
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	4
Master Carton Bar Code	50849489003165
Master Carton Dimensions (L x W x H in.)	15.67 x 9.92 x 9.45
Master Carton Dimensions (L x W x H cm.)	398 x 252 x 240
Master Carton Weight (lbs)	6.1
Pallet Quantity	192

COMPATIBILITY

Dimmers:

Lutron: TG-603PGH-WH, DVW-604PGH-WH, MSCL-OP153M-WH, GL-600H-DK, S-600P

Leviton: 81000-I

Cooper: SCL03P-A-K

Cans:

Commercial Electric: H1, H2, H3, H4, H5, H6, H7, H8, H15, H16, H17, H18, H21

Juno: IC20, IC21, IC22, IC20R, IC2R, IC22R

Halo: H5T, H5RT, H5ICAT, H5RICAT, H5ICT, H5RICT, H7RICT, H7ICAT, H7RICAT, H7ICT, H7T, H7RT, H27ICT, H27T, H27RT, H750ICAT, H750RICAT

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etiled.us/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256