

# 5 5/8" AC Power Recessed Downlight

670 lm | 120VAC | Ordering 53193111 | Part DL-6-11-830-SV-D

- > Energy Saving 9 Watt Integrated LED
- > Uses 84% Less Energy than Equivalent 65 Watt Incandescent Bulb
- > Warm White 3000K CCT
- > Lasts 45 years\* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty
- > IC Rated for Direct Contact with Insulation



## SPECIFICATIONS

Ordering	53193111
Part	DL-6-11-830-SV-D
Description	5 5/8" AC Power Recessed Retrofit Downlight Kit
Input Voltage (VAC)	120
Wattage	9
Dimmability	Triac
Average Rated Life <sup>1</sup>	50,000 hours
Typical Lumens <sup>2</sup>	670
CCT <sup>3</sup>	3000K
Location Rating	UL Wet
CRI <sup>4</sup>	80
Beam Angle	100
Operating Temperature	Min -4°F (-20° C), Max 113°F (45° C)
Power Factor	>0.9
R9	12
DUV	-0.00084
CBCP	311
Operating Frequency (Hz)	60

1 Hours lifetime with 70% lumen maintenance  
 2 Thermally stable typical lumens (±10%)  
 3 Thermally stable CCT (±10%)  
 4 Color rendering index/Ra

ETI

**LED lighting facts**

<b>Light Output (Lumens)</b>	<b>670</b>
<b>Watts</b>	<b>10.5</b>
<b>Lumens per Watt (Efficacy)</b>	<b>63.81</b>
<b>Color Accuracy</b>	
Color Rendering Index (CRI)	<b>80</b>
<b>Light Color</b>	
Correlated Color Temperature (CCT)	<b>3000 (Bright White)</b>

2700K    3000K    4500K    6500K

All results are according to IESNA LM-79-2008. Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: 5BAM-LEK2W (2/8/2018)  
 Model Number: 53193111#W=11-30  
 Type: Retrofit Kit - Downlight

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
 Call: 1.855.ETi.SSLI  
 1.855.384.7754





# 5 7/8" AC Power Recessed Downlight

670 lm | 120VAC | Model 53193111 | Part DL-6-11-830-SV-D

## SHIPPING INFORMATION

Ordering	53193111
Part	DL-6-11-830-SV-D
UPC	849489003542
Product Dimensions (W x H in.)	7 1/2 x 2 1/4
Product Dimensions (W x H cm.)	19 x 5 1/2
Product Weight (lbs.)	0.77
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	4
Master Carton Bar Code	50849489003547
Master Carton Dimensions (L x W x H in.)	10 x 9 x 10
Master Carton Dimensions (L x W x H cm.)	242 x 217 x 262
Master Carton Weight (lbs)	1.84
Pallet Quantity	320

## COMPATIBILITY

### Dimmers:

Lutron: CT-603PGH-WH, GL-600H-DK, MSCL-OP153M, MACL-153MH-WH, SCL-153PR-WH, TGCL-153PR-WH, TGCL-153PH-WH, TG-603PGH-WH, AYCL-153P-WH  
Leviton: CD-C22-06672-12A, CD-R62-06674-12A, CD-R50-IPL06-12A, SB-011-IPL06-22A, 8100-I  
Legrand: ADWR703HW4, ADPD453LM2  
Cooper: DLC03PA-PTA, 9573A-PTA

### Cans:

Commercial Electric: H1, H2, H3, H4, H5, H6, H7, H8, H15, H16, H17, H18, H21  
Juno: IC20, IC21, IC22, IC20R, IC2R, IC22R  
Halo: H5T, H5RT, H5ICAT, H5RICAT, H5ICT, H5RICT, H7RICT, H7ICAT, H7RICAT, H7ICT,

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.etiled.us/fcc15b](http://www.etiled.us/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

**ETi Solid State Lighting, Inc.**  
720 Corporate Woods Parkway  
Vernon Hills, IL 60061  
Phone: 855.384.7754  
Fax: 847.383.6256