



# 5 1/8" AC Power Recessed Downlight

670 lm | 120VAC | Ordering 53193141 | Part DL-6-11-840-SV-D

- > Energy Saving 9 Watt Integrated LED
- > Uses 84% Less Energy than Equivalent 65 Watt Incandescent Bulb
- > Cool White 4000K CCT
- > Lasts 45 years\* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty
- > IC Rated for Direct Contact with Insulation



## SPECIFICATIONS

Ordering	53193141
Part	DL-6-11-840-SV-D
Description	5 1/8" AC Power Recessed Retrofit Downlight Kit-Dimmable
Input Voltage (VAC)	120
Wattage	9
Dimmability	Triac
Average Rated Life <sup>1</sup>	50,000 hours
Typical Lumens <sup>2</sup>	670
CCT <sup>3</sup>	4000K
Location Rating	UL Wet
CRI <sup>4</sup>	80
Beam Angle	100
Operating Temperature	Min -4°F (-20° C), Max 113°F (45° C)
Power Factor	>0.9
R9	10
DUV	0.0008
CBCP	289
Operating Frequency (Hz)	60

1 Hours lifetime with 70% lumen maintenance  
 2 Thermally stable typical lumens (±10%)  
 3 Thermally stable CCT (±10%)  
 4 Color rendering index/Ra

ETI

**LED lighting facts**  
A Program of the U.S. DOE

Light Output (Lumens)	670
Watts	10.5
Lumens per Watt (Efficacy)	63.81

---

**Color Accuracy**  
Color Rendering Index (CRI) 80

---

**Light Color**  
Correlated Color Temperature (CCT) 4000 (Bright White)

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: YN84-6R17GD (8/11/2017)  
 Model Number: 531931##(##=41-50)  
 Type: Luminaire - Downlight

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
 Call: 1.855.ETi.SSLI  
 1.855.384.7754





# 5 5/8" AC Power Recessed Downlight

670 lm | 120VAC | Ordering 53193141 | Part DL-6-11-840-SV-D



## SHIPPING INFORMATION

Ordering	53193141
Part	DL-6-11-840-SV-D
UPC	849489006413
Product Dimensions (W x H in.)	7 1/2 x 2 1/8
Product Dimensions (W x H cm.)	19 x 5 1/2
Product Weight (lbs.)	0.77
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	4
Master Carton Bar Code	50849489006418
Master Carton Dimensions (L x W x H in.)	10 x 10 x 9
Master Carton Dimensions (L x W x H cm.)	262 x 242 x 217
Master Carton Weight (lbs)	1.84
Pallet Quantity	448

## COMPATIBILITY

### Dimmers:

Lutron: CT-603PGH-WH, GL-600H-DK, MSCL-OP153M, MACL-153MH-WH, SCL-153PR-WH, TGCL-153PR-WH, TGCL-153PH-WH, TG-603PGH-WH, AYCL-153P-WH  
 Leviton: CD-C22-06672-12A, CD-R62-06674-12A, CD-R50-IPL06-12A, SB-011-IPL06-22A, 8100-I

Legrand: ADWR703HW4, ADPD453LM2

Cooper: DLC03PA-PTA, 9573A-PTA

### Cans:

Commercial Electric: H1, H2, H3, H4, H5, H6, H7, H8, H15, H16, H17, H18, H21

Juno: IC20, IC21, IC22, IC20R, IC2R, IC22R

Halo: H5T, H5RT, H5ICAT, H5RICAT, H5ICT, H5RICT, H7RICT, H7ICAT, H7RICAT, H7ICT,

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.etiled.us/fcc15b](http://www.etiled.us/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
 Call: 1.855.ETi.SSLI  
 1.855.384.7754

**ETi Solid State Lighting, Inc.**  
 720 Corporate Woods Parkway  
 Vernon Hills, IL 60061  
 Phone: 855.384.7754  
 Fax: 847.383.6256