



4' Linkable Shop Light

3600 lms | 120 VAC | Model 54103162 | Part SH-48-840K-SV

- > Energy Saving 36 Watt Integrated LED
- > Cool White 4000k CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



SPECIFICATIONS

Model	54103162
Part	SH-48-840K-SV
Description	4' Linkable Shop Light
Input Voltage (VAC)	120
Wattage	36
Dimmability	NA
Average Rated Life ¹	50,000 hours
Typical Lumens ²	3600
CCT ³	4000k
Location Rating	UL Damp
CRI ⁴	80
Beam Angle	110°
Operating Temperature	Min -4°F (-20° C), Max 113°F (45° C)
Power Factor	>0.9
R9	22
DUV	-0.0010
CBCP	1135
Operating Frequency (Hz)	60

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra

TO ORDER:

www.ETISSL.com

Call: 1.855.ETI.SSLI

1.855.384.7754





4' Linkable Shop Light

3600 lms | 120 VAC | Model 54103162 | Part SH-48-840K-SV

SHIPPING INFORMATION

Model	54103162
Part	SH-48-840K-SV
UPC	849489009319
Product Dimensions (L x W x H in.)	48.03 x 5.75 x 2.44
Product Dimensions (L x W x H cm.)	122 x 14.6 x 6.2
Product Weight (lbs.)	3.48
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	4
Master Carton Bar Code	50849489009314
Master Carton Dimensions (L x W x H in.)	51.97 x 14.25 x 6.22
Master Carton Dimensions (L x W x H cm.)	132 x 36.2 x 15.8
Master Carton Weight (lbs)	21.45
Pallet Quantity	96

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETISSL.com/fcc15b

TO ORDER:
www.ETISSL.com
Call: 1.855.ETI.SSLI
1.855.384.7754

ETI Solid State Lighting, Inc.
720 Northgate Parkway
Wheeling, IL 60090
Phone: 855.384.7754
Fax: 847.383.6256