



4' T8 Direct Replacement Tube

2160 lms | Ballast Driven | Ordering 54140341 | Part T8BC-4-20-840-MV-P

- > Base G13 Bi-Pin
- > Cool White 4000K CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



SPECIFICATIONS

| | |
|---------------------------------|---|
| Ordering | 54140341 |
| Part | T8BC-4-20-840-MV-P |
| Certification | 54140341 |
| Description | 4' T8 Direct Replacement Tube |
| Input Voltage (VAC) | Ballast Driven |
| Wattage | 20 |
| Dimmability | Non-Dimmable |
| Average Rated Life ¹ | 50,000 hours |
| Typical Lumens ² | 2160 |
| CCT ³ Location | 4000K |
| Rating | UL Damp |
| CRI ⁴ | 80 |
| Beam Angle Operating | 120 |
| Temperature | Min -4°F (-20° C), Max 113°F (45° C) |
| Power Factor | >0.9 |
| R9 | 6 |
| DUV | 0.00135 |
| Operating Frequency (Hz) | 50/60 |

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra

TO ORDER:

www.ETiSSL.com

Call: 1.855.ETi.SSLI

1.855.384.7754





4' T8 Direct Replacement Tube

2160 Ims | Ballast Driven | Ordering 54140341 | Part T8BC-4-20-840-MV-P

SHIPPING INFORMATION

| | |
|--|--------------------|
| Ordering | 54140341 |
| Part | T8BC-4-20-840-MV-P |
| UPC | 849489002156 |
| Product Dimensions (L x W x H in.) | 47 x 1 1/8 x 1 1/8 |
| Product Dimensions (L x W x H cm.) | 119.8 x 2.9 x 2.9 |
| Product Weight (lbs.) | 0.51 |
| Inner Carton Quantity | N/A |
| Inner Carton Bar Code | N/A |
| Inner Carton Dimensions (L x W x H in.) | N/A |
| Inner Carton Dimensions (L x W x H cm.) | N/A |
| Inner Carton Weight (lbs) | N/A |
| Master Carton Quantity | 24 |
| Master Carton Bar Code | 50849489002151 |
| Master Carton Dimensions (L x W x H in.) | 50.43 x 9.84x 6.93 |
| Master Carton Dimensions (L x W x H cm.) | 128.1 x 25 x 17.6 |
| Master Carton Weight (lbs) | 15.64 |
| Pallet Quantity | 864 |

COMPATIBILITY

Ballasts:

| Ballast Brand | Ballast Model# | Ballast Brand | Ballast Model# |
|---------------|-----------------------|---------------|--------------------------|
| OSRAM | QHE 1X32T8/UNV ISL-SC | OSRAM | QHE 3X32T8/UNV ISL-SC |
| OSRAM | QHE 1X32T8/UNV ISN-SC | OSRAM | QHE 2X32T8/UNV ISL-SC |
| OSRAM | QTP 1X32T8/UNV ISN-SC | OSRAM | QTP 2X32T8/UNV ISL-SC |
| OSRAM | QHE 4X32T8/UNV ISL-SC | OSRAM | QHE 2X32T8/UNV ISH HT-SC |
| OSRAM | QHE 4X32T8/UNV PSN-SC | OSRAM | QHE 2X32T8/UNV ISN-SC |
| OSRAM | QHE 4X32T8/UNV ISN-SC | OSRAM | QTP 2X32T8/UNV ISH-SC |
| OSRAM | QHE 4X32T8/UNV ISH-SC | OSRAM | QTP 2X32T8/UNV ISN-SC |
| OSRAM | QTP 3X32T8/UNV ISL-SC | FULHAM | FH7-UNV-500L-CEC |
| OSRAM | QTP 3X32T8/UNV ISN-SC | FULHAM | ILADL7 |
| OSRAM | QHE 3X32T8/UNV ISN-SC | IOTA | I-320-TBTS |
| OSRAM | QHE 3X32T8/UNV ISH-SC | | |

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER:
www.ETiSSL.com
 Call: 1.855.ETi.SSLI
 1.855.384.7754

ETi Solid State Lighting, Inc.
 720 Corporate Woods Parkway
 Vernon Hills, IL 60061
 Phone: 855.384.7754
 Fax: 847.383.6256