



4' T8 Direct Replacement Tube

2200 lms | Ballast Driven | Ordering 54140361 | Part T8BC-4-20-850-MV-P

- > Base G13 Bi-Pin
- > Daylight 5000K CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



SPECIFICATIONS

Ordering	54140361
Part	T8BC-4-20-850-MV-P
Certification	54140361
Description	4' T8 Direct Replacement Tube
Input Voltage (VAC)	Ballast Driven
Wattage	20
Dimmability	Non-Dimmable
Average Rated Life ¹	50,000 hours
Typical Lumens ²	2200
CCT ³	5000K
Location Rating	UL Damp
CRI ⁴	80
Beam Angle Operating	120
Temperature	Min -4°F (-20° C), Max 113°F (45° C)
Power Factor	>0.9
R9	14
DUV	0.00305
Operating Frequency (Hz)	50/60

1 Hours lifetime with 70% lumen maintenance

2 Thermally stable typical lumens (±10%)

3 Thermally stable CCT (±10%)

4 Color rendering index/Ra

TO ORDER:

www.ETiSSL.com

Call: 1.855.ETi.SSLI

1.855.384.7754





4' T8 Direct Replacement Tube

2200 lms | Ballast Driven | Ordering 54140361 | Part T8BC-4-20-850-MV-P

SHIPPING INFORMATION

Ordering	54140361
Part	T8BC-4-20-850-MV-P
UPC	849489002163
Product Dimensions (L x W x H in.)	47 x 1 1/8 x 1 1/8
Product Dimensions (L x W x H cm.)	119.8 x 2.9 x 2.9
Product Weight (lbs.)	0.51
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	24
Master Carton Bar Code	50849489002168
Master Carton Dimensions (L x W x H in.)	50.43 x 9.84 x 6.93
Master Carton Dimensions (L x W x H cm.)	128.1 x 25 x 17.6
Master Carton Weight (lbs)	15.64
Pallet Quantity	864

COMPATIBILITY

Ballasts:

Ballast Brand	Ballast Model#	Ballast Brand	Ballast Model#
OSRAM	QHE 1X32T8/UNV ISL-SC	OSRAM	QHE 3X32T8/UNV ISL-SC
OSRAM	QHE 1X32T8/UNV ISN-SC	OSRAM	QHE 2X32T8/UNV ISL-SC
OSRAM	QTP 1X32T8/UNV ISN-SC	OSRAM	QTP 2X32T8/UNV ISL-SC
OSRAM	QHE 4X32T8/UNV ISL-SC	OSRAM	QHE 2X32T8/UNV ISH HT-SC
OSRAM	QHE 4X32T8/UNV PSN-SC	OSRAM	QHE 2X32T8/UNV ISN-SC
OSRAM	QHE 4X32T8/UNV ISN-SC	OSRAM	QTP 2X32T8/UNV ISH-SC
OSRAM	QHE 4X32T8/UNV ISH-SC	OSRAM	QTP 2X32T8/UNV ISN-SC
OSRAM	QTP 3X32T8/UNV ISL-SC	FULHAM	FH7-UNV-500L-CEC
OSRAM	QTP 3X32T8/UNV ISN-SC	FULHAM	ILADL7
OSRAM	QHE 3X32T8/UNV ISN-SC	IOTA	I-320-TBTS
OSRAM	QHE 3X32T8/UNV ISH-SC		

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER:
www.ETiSSL.com
 Call: 1.855.ETi.SSLI
 1.855.384.7754

ETi Solid State Lighting, Inc.
 720 Corporate Woods Parkway
 Vernon Hills, IL 60061
 Phone: 855.384.7754
 Fax: 847.383.6256