



4' DIMMABLE VAPOR TIGHT **SUPERIOR** VALUE & PERFORMANCE



PRODUCT OVERVIEW

ETi SSL's 4ft. Dimmable Vapor Tight is designed with durable stainless-steel latches to prevent moisture and dirt from compromising the housing and damaging interior wires and components inside the fixture. Vapor Tights are weatherproof and rated IP65 as dust tight and protect against projected water. This Vapor Tight is dimmable from 0-10V. It comes with mounting brackets and can be suspended or ceiling mounted, depending on desired installation.

Our Dimmable Vapor Tight is DLC listed and delivers 5,865 lumens of extremely uniform ambient 5000K illumination. Installation is quick and easy with direct wiring and plug in options. Fixture is rated to operate reliably from -30° C (-22° F) and in high ambient 60° C (140° F) applications. The 4ft. Dimmable Vapor Tight provides long-lasting maintenance free operation thanks to its reported 91.46% lumen maintenance @ 54,000 hours and projected L70 @ 210,000 hours. Ideal residential and commercial applications include, but are not limited to offices, multi-family, hallways and corridors, garages, storage rooms, workshops and more.

Our entire team takes great pride in our dedication to providing innovative in-stock lighting solutions that typically ship in 2-3 days with the product reliability and quality that you can always depend on from ETi SSL.

STOCK ORDERING INFORMATION (typical 2-3 day shipment lead time)¹

Catalog Logic/PT#	Model #	UPC	Size	Lumens	Wattage	LPW	CCT	CRI	Voltage	Dimming	DLC ²
VT-4-54-850-MV-D	54465161	849489002293	4'	5,865	51	115	5000K	80 (min)	120-277V	0-10V	Yes

Notes:


1. Stock SKUs typically ship in 24-48 hours upon receipt of an approved released order.
2. Search first 6-digits of the model # followed by '##' on the DLC QPL...Ex. '545981##' to view DLC qualified SKUs

VT Series

4' Dimmable Vapor Tight

Model#54465161 | 5,865 Lumens | 51W | 115LPW | 5000K | DLC | 5 Year Warranty

KEY DIMENSIONAL INFORMATION



Note: All dimensions are shown in inches (millimeters).


PHOTOMETRIC DETAILS

Luminaire Data: VT-4-54-850-MV-D

IES File Name	54465161-2.IES
CCT & CRI	5000K, 80CRI minimum
Initial Delivered Lumens	5,843
Wattage	47.0W
Efficacy	124
Beam Angle	50% = 125.7° 10% = 163.9°
Spacing	0° = 1.30 90° = 1.32

Photometric values based on tests performed in compliance with LM-63 & LM-79.

Indoor Candela Plot



Shipping Information

Unit Weight ¹	Size	Pallet ²
4.3 lbs	4' unit	160 units

1. Case pack weighs 8.6 lbs (2 units / per case pack).
2. There are 80 case packs per pallet.

AVAILABLE STOCK ACCESSORIES (must be ordered separately)



Emergency LED Driver/BBU (field installed)

Catalog Logic/PT#	Model #	Description
EMA25FY-170 (G2)	70112202	25W, IP rated, 90 minutes, Square
EMUFO-40170-YY (G2)	70114401	40W, IP rated, 90 minutes, Round
EMUFO-25170-YY (G3)	70112201-2	25W, IP rated, 90 minutes, Round
EMUFO-40170-YY (G3)	70114401-2	40W, IP rated, 90 minutes, Round
EMA25FY-170 (G3)	70112202-2	25W, IP rated, 90 minutes, Square
EMA40FY-170 (G3)	70114402-2	40W, IP rated, 90 minutes, Square
MC601V	90600144	IP20, UL listed, Square

MISC. PRODUCT SPECS & DETAILS

Load Information

Power Factor	> 0.90
THD	< 20%
Frequency	50/60 Hz
Sound Rating	< 20 dBA
Low Temp Start	-30° C (-22° F)
Max Temp	60° C (140° F)
Unit Weight	4.3 lbs

Lumen Maintenance

Ambient Temperature	TM-21 Lumen Maintenance (54,000 hours)
25° C (77° F)	> 91.46%
Ambient Temperature	TM-21 Theoretical L70 (hours)
25° C (77° F)	210,000