



4' T8 Direct Replacement Tube

2000 lm | Ballast Driven | Model 54217131 | Part T8BC-4-16-835-MV

- > Base G13 Bi-Pin
- > Cool White 3500K CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



SPECIFICATIONS

Model	54217131
Part	T8BC-4-16-835-MV
Description	4' T8 Direct Replacement Tube
Input Voltage (VAC)	Ballast Driven
Wattage	16
Dimmability	Non-Dimmable
Average Rated Life ¹	50,000 hours
Typical Lumens ²	2000
CCT ³	3500K
Location Rating	UL Damp
CRI ⁴	80
Beam Angle	110°
Operating Temperature	Min -4°F (-20° C) Max 115°F (45° C)
Power Factor	> 0.9
R9	12
DUV	-0.00016
Operating Frequency (Hz)	50/60

1 Hours lifetime with 70% lumen maintenance

2 Thermally stable typical lumens (±10%)

3 Thermally stable CCT (±10%)

4 Color rendering index/Ra

TO ORDER:

www.ETiSSL.com

Call: 1.855.ETi.SSLI

1.855.384.7754





4' T8 Direct Replacement Tube

2000 lms | Ballast Driven | Model 54217131 | Part T8BC-4-16-835-MV

SHIPPING INFORMATION

Model	54217131
Part	T8BC-4-16-835-MV
UPC	849489009124
Product Dimensions (L x W x H in.)	47 1/4 x 1 1/16 x 1 1/16
Product Dimensions (L x W x H cm.)	119.9 x 2.9 x 2.9
Product Weight (lbs.)	0.51
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	24
Master Carton Bar Code	50849489009129
Master Carton Dimensions (L x W x H in.)	4' 2 7/16" x 9 27/32" x 6 15/16"
Master Carton Dimensions (L x W x H cm.)	128.1 x 25.0 x 17.6
Master Carton Weight (lbs)	15.43
Pallet Quantity	576

COMPATIBILITY

Ballasts:

PHILIPS: ICN-1P32-N, ICN-2P32-N, IOPA-2P32-LW-N

GE UltraMax: GE232MAXP-H/ULTRA, GE432MAXP-H/ULTRA, GE432MAXP-L/ULTRA

ACCUPRO: AP-232IP-UNV

SYLVANIA: QHE 4*32T8/UNV PSH-SC

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256