



# 4' T8 Direct Replacement Tube

2000 lms | Ballast Driven | Model 54217141 | Part T8BC-4-16-840-MV

- > Base G13 Bi-Pin
- > Cool White 4000k CCT
- > Lasts 45 years\* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



## SPECIFICATIONS

Model	54217141
Part	T8BC-4-16-840-MV
Description	4' T8 Direct Replacement Tube - Non-Dimmable
Input Voltage (VAC)	Ballast Driven
Wattage	16
Dimmability	Non
Average Rated Life <sup>1</sup>	50,000 hours
Typical Lumens <sup>2</sup>	2000
CCT <sup>3</sup>	4000k
Location Rating	UL Damp
CRI <sup>4</sup>	80
Beam Angle	120
Operating Temperature	Min -4°F (-20° C), Max 115°F (45° C)
Power Factor	>0.9
R9	6.6
DUV	.0012
Operating Frequency (Hz)	50/60

1 Hours lifetime with 70% lumen maintenance

2 Thermally stable typical lumens (±10%)

3 Thermally stable CCT (±10%)

4 Color rendering index/Ra

## TO ORDER:

[www.ETiSSL.com](http://www.ETiSSL.com)

Call: 1.855.ETi.SSLI

1.855.384.7754





# 4' T8 Direct Replacement Tube

2000 lms | Ballast Driven | Model 54217141 | Part T8BC-4-16-840-MV

## SHIPPING INFORMATION

Model	54217141
Part	T8BC-4-16-840-MV
UPC	849489005591
Product Dimensions (L x W x H in.)	47.2 x 1.14 x 1.14
Product Dimensions (L x W x H cm.)	1198 x 29 x 29
Product Weight (lbs.)	0.51
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	15
Master Carton Bar Code	50849489005596
Master Carton Dimensions (L x W x H in.)	52.2 x 11.89 x 8.5
Master Carton Dimensions (L x W x H cm.)	1326 x 302 x 216
Master Carton Weight (lbs)	14.11
Pallet Quantity	315

## COMPATIBILITY

### Ballasts:

PHILIPS: ICN-1P32-N, ICN-2P32-N, IOPA-2P32-LW-N

GE UltraMax: GE232MAXP-H/ULTRA, GE432MAXP-H/ULTRA, GE432MAXP-L/ULTRA

ACCUPRO: AP-232IP-UNV

SYLVANIA: QHE 4\*32T8/UNV PSH-SC

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.etiled.us/fcc15b](http://www.etiled.us/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

**ETi Solid State Lighting, Inc.**  
720 Corporate Woods Parkway  
Vernon Hills, IL 60061  
Phone: 855.384.7754  
Fax: 847.383.6256