



4' T8 Integral Glass Tube

2200 lms | 120-277VAC | Model 54296441 | Part T8BP-4-15-840-MV-22

- > Base G13 Bi-Pin
- > Cool Light 4000k CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



SPECIFICATIONS

Model	54296441
Part	T8BP-4-15-840-MV-22
Description	4' T8 Integral Glass Tube - Non-Dimmable
Input Voltage (VAC)	120-277
Wattage	15
Dimmability	Non-Dim
Average Rated Life ¹	50,000 hours
Typical Lumens ²	2200
CCT ³	4000k
Location Rating	UL Damp
CRI ⁴	80
Beam Angle	120
Operating Temperature	Min -4°F (-20° C), Max 115°F (45° C)
Power Factor	>0.9
R9	12
DUV	.0005
Operating Frequency (Hz)	50/60

- 1 Hours lifetime with 70% lumen maintenance
- 2 Thermally stable typical lumens (±10%)
- 3 Thermally stable CCT (±10%)
- 4 Color rendering index/Ra

LED lighting facts
A Program of the U.S. DOE

Light Output (Lumens)	2200
Watts	15
Lumens per Watt (Efficacy)	146.67
Color Accuracy Color Rendering Index (CRI)	80
Light Color Correlated Color Temperature (CCT)	4000 (Bright White)

Warm White | Bright White | Daylight
2700K | 3000K | 4500K | 6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: 5BAM-3CD468 (Revised 9/19/2016)
Model Number: 542964XX(XX=41-50)
Type: Retrofit Kit - Linear

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754



E349551



4' T8 Integral Glass Tube

2200 lms | 120-277VAC | Model 54296441 | Part T8BP-4-15-840-MV-22

SHIPPING INFORMATION

Model	54296441
Part	T8BP-4-15-840-MV-22
UPC	849489005775
Product Dimensions (L x W x H in.)	47.17 x 1.14 x 1.14
Product Dimensions (L x W x H cm.)	1198 x 29 x 29
Product Weight (lbs.)	0.51
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	24
Master Carton Bar Code	50849489005770
Master Carton Dimensions (L x W x H in.)	50.43 x 9.84 x 6.93
Master Carton Dimensions (L x W x H cm.)	1281 x 250 x 176
Master Carton Weight (lbs)	15.64
Pallet Quantity	864

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.eted.us/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256