

## SPECIFICATIONS

The 120/277V Step Dimming Motion Sensor with advance controls is ideal for T24 regulated environments, as the motion sensor meets most lighting control guidelines, that need daylight and time delays, and is easily controlled. They are perfect for rooms where lights are often left on, such as an office, or rooms that you often enter with your hands full, such as a laundry room or supply closet. Warranty period 5 years. Suitable for installations from -4° F 140° F.




Typical applications includes indoor warehouse, gymnasium, recreational space, retail, public spaces, schools, loading dock, garages and assembly lines and production facilities.

### KEY FEATURES & BENEFITS

- Operating Voltage: 120/277V
- Hold Time: 10s~30min
- Mounting Height: 49FT
- Protection Level: IP20
- Daylight Sensor: 5lux/10lux/30lux/50lux/Disable
- Stand-by dimming level: 10%/20%/30%/40%/50%
- Rated load: 800W (inductive), 1200W (resistive)
- Detection Angle: 150° (wall installation), 360° (ceiling installation)

### FIXTURE DIMENSIONS



SKU# 90600144  
Dimension A= 4.00"  
Dimension B= 2.05"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.etissl.us/fcc15b](http://www.etissl.us/fcc15b)

# Step Dimming Motion Sensor

## 90600144

### SPECIFICATION DATA

Item Number	Description	Input Voltage (VAC)	Average Rated Life <sup>1</sup>	Typical Lumens <sup>2</sup>	CCT <sup>3</sup>	CRI <sup>4</sup>	Power Factor	R9	DUV	CBCP	Beam	Operating Frequency
90600144	Step Dimming Motion Sensor	120/277	50,000 hours	/	/	/	/	/	/	/	/	50/60Hz

<sup>1</sup> Hours lifetime with 70% lumen maintenance

<sup>2</sup> Thermally stable typical lumens

<sup>3</sup> Thermally stable CCT

<sup>4</sup> Color rendering index/Ra

### SHIPPING INFORMATION

Item Number	Item UPC	Item Dimensions (L x W x H)	Item Weight (lbs)	Inner Pack Qty	Inner Carton Bar Code	Inner Carton Dimensions (L x W x H)	Inner Pack Weight (lbs)	Master Pack QTY	Master Carton Bar Code	Master Dimensions (L x W x H)	Master Pack Weight (lbs)
90600144	849489 009742	4.00" x 2.05" x 1.00"	/	4	3084948 9009743	6.38" x 4.84" x 2.36"	1.1	60	5084948 9009747	20.08" x 12.83" x 5.55"	18.73

### COMPATIBLE LIST

Category	SKU#
Wrap Light	WR-4-40-840-MV-D WR-4-40-840-MV-D-EM WR-4-57-840-MV-D WR-2-20-840-MV-D



The Americas Headquarters  
720 Corporate Woods Parkway  
Vernon Hills, IL 60061  
855-384-7754  
[www.etissl.com](http://www.etissl.com)