



Step Dimming Motion Sensor

120-277VAC | Model 70201101 | Part MC031V-D

- > Comes with a 5 year warranty.
- > Operating Voltage: 120/277V/50/60HZ
- > IP65
- > Daylight Sensor: 50lux/100lux/200lux/Disable
- > Hold Time: 5s/5min/10min/30min/1h/Disable
- > Rated load: 120Vac 4A electronic / magnetic ballast
- 277Vac 3A electronic / magnetic ballast
- > Detection Sensitivity: 50% / 100%



SPECIFICATIONS

Model	70201101
Certification	70201101
Description	Step Dimming Motion Sensor
Input Voltage (VAC)	120-277V
Wattage	NA
Dimmability	NA
Average Rated Life ¹	50,000
Typical Lumens ²	NA
CCT ³	NA
Location Rating	NA
CRI ⁴	NA
Beam Angle	NA
Operating Temperature	-31°F (-35°C) to 158°F (70°C)

1 Hours lifetime with 70% lumen maintenance

2 Thermally stable typical lumens (±10%)

3 Thermally stable CCT (±10%)

4 Color rendering index/Ra

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754





Step Dimming Motion Sensor

120-277VAC | Model 70201101 | Part MC031V-D

SHIPPING INFORMATION

Ordering	70201101
UPC	NA
Product Dimensions (W x H in.)	2.3 x 4.7
Product Dimensions (W x H cm.)	5.8 x 12
Product Weight (lbs.)	NA
Inner Carton Quantity	1
Inner Carton Bar Code	NA
Inner Carton Dimensions (L x W x H in.)	NA
Inner Carton Dimensions (L x W x H cm.)	NA
Inner Carton Weight (lbs)	NA
Master Carton Quantity	50
Master Carton Bar Code	NA
Master Carton Dimensions (L x W x H in.)	NA
Master Carton Dimensions (L x W x H cm.)	NA
Master Carton Weight (lbs)	NA
Pallet Quantity	N/A

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER:
www.ETiSSL.com
Call: **1.855.ETi.SSLI**
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Northgate Parkway
Wheeling, IL 60090
Phone: 855.384.7754
Fax: 847.383.6256

Spec Sheet 70201101 | 2020.02.27 US