

CWPK | FULL CUTOFF WALL PACK

WITH DUSK-TO-DAWN PHOTOCELL

3 Lumen Boost[®] | 3 CCT Color Preference[®]

KEY FEATURES

ETi SSL's full cutoff design maximizes light distribution and application spacing, while eliminating uplight. It features a Dusk-to-Dawn photocell w/ enable/disable capability, three selectable CCTs and three selectable wattages—giving you flexibility and efficiency.

CCT & Light Quality

- 3 Selectable CCTs (3000K, 4000K, 5000K)
- 80+ CRI

Light Output & Efficacy

- 3 Lumen Packages and 2 Lumen Boost Levels:
Lumen Package 1: 2800 – 8600 lm
Lumen Package 2: 8400 – 14000 lm
- Efficacy: Up to 152 LPW

Dimming, Voltage, Controls

- Integrated 0-10V dimming
- Universal voltage (120–277V), 50/60Hz
- Dusk to Dawn Photocell w/ enable/disable standard

SPECIFICATIONS

Construction

- Corrosion resistant, rugged die-cast aluminum housing with bronze powder coat paint finish
- Hinged housing allows for easy access to wiring, photocell, wattage and CCT select

Optics

- Type 4 distribution
- 2 Selectable Lumen Packages from 8600 to 14000 Lumens at highest wattage
- PMMA TIR (Total Internal Reflectance Lens) provides diffused, uniform light quality

Electrical, Operating Temp.

- Universal 120-277 VAC input voltage, 50/60Hz
- Power factor >90%, THD <20%
- Operating Temperature Range: -40° C (-40° F) / 50° C (122° F)
 Sensor Temperature Range: -25° C TO 50° C (-13° F) / 50° C (122° F)

Warranty

- Five-year limited warranty

KEY DATA	
Delivered Lumen Range	2948 – 13856
Wattage Range	19.4 – 104.3
Efficacy Range (LPW)	120 – 152
Reported Life (Hours)	L70 / > 50,000

DATE:	PROJECT:
TYPE:	NOTES:
CATALOG #:	



Hinged Access
for wiring,
Wattage & CCT
select access



Photocell
w/cover
+ enable
disable
capability



**DUSK
TO
DAWN**



**Color
Preference[®]**

**3 LUMEN
BOOST[®]**

Certifications & Test Data

- UL/cUL listed and built for wet location
- IP65 Rated
- DesignLights Consortium™ Qualified and classified for DLC Standard (all lumen packages), refer to www.designlights.org for details
- Estimated > 54,000 hours LED lifespan based on IES LM-80 results and TM-21 calculations



Full Cutoff Wall Pack WITH DUSK-TO-DAWN PHOTOCELL | 3 LUMEN BOOST® | 3 CCT COLOR PREFERENCE®

ORDERING GUIDE

OPTIONS

CWPK

Series

CWPK
Cutoff
Wall Pack

-

Lumens

(Lumen Package)¹

1
2800 – 8600 lm

2
8400 – 14000 lm

-

LB3

Lumen Boost

LB3
3 Lumen Boost®

Lumen Pkg #1:
20 | 40 | 60W

Lumen Pkg #2:
60 | 80 | 100W

-

CP3

CCT

CP3
3 CCT
Color Preference®
3/4/5000K

-

MV

Voltage

MV
Multi-Volt
120-277V

-

LVD

Dimming

LVD
Low Voltage
Dimming
0-10V

-

BBU

BBU

EM²
Emergency
Battery 8W
(Leave Blank)
No BBU

Notes:
1. Lumen package ranges are approximate values. For actual delivered lumen data, please see below.
2. BBU options are MTO only, longer lead times apply.

STOCK ORDERING INFORMATION

Catalog Part Number	Order Number	Description	CRI	CCT (CP3)	Wattage Level	Delivered Lumens ¹	LPW	Volt.	Dim	Bug Rating ²			DLC ³
										B	U	G	
CWPK-1-LB3-CP3-MV-LVD	61511101	Cutoff Wall Pack, Lumen Package 1	80+	3000K	60	8255	132	120-277V	0-10V	2	0	2	Premium
					40	5661	142						
					20	2948	148						
				4000K	60	8578	142						
					40	5826	149						
					20	2955	152						
				5000K	60	7806	120						
					40	5482	134						
					20	2880	144						
CWPK-2-LB3-CP3-MV-LVD	61512101	Cutoff Wall Pack, Lumen Package 2	80+	3000K	100	13242	131	120-277V	0-10V	3	0	2	Premium
					80	10924	135						
					60	8545	141						
				4000K	100	13856	142						
					80	11427	146						
					60	8888	150						
				5000K	100	12658	121						
					80	10647	128						
					60	8466	136						

Notes: 1. For more delivered lumens, download ies files from ETISSL.com
2. BUG rating based on highest wattage level @4000K. See ies files for more data
3. DLC search by catalog part number

MADE-TO-ORDER PRODUCT INFO (Longer lead times apply. Contact ETi for details.)

Catalog Part Number	Order Number	Description
CWPK-1-LB3-CP3-MV-LVD-EM	61511101-EM	Cutoff Wall Pack, Lumen Package 1 with 8W Battery Backup
CWPK-2-LB3-CP3-MV-LVD-EM	61512101-EM	Cutoff Wall Pack, Lumen Package 2 with 8W Battery Backup

Full Cutoff Wall Pack WITH DUSK-TO-DAWN PHOTOCELL | 3 LUMEN BOOST® | 3 CCT COLOR PREFERENCE®

BBU ACCESSORIES¹

Catalog Part Number	Model Number	Description
WPK-EM	70124101	Cutoff Wall Pack 8W Emergency Battery

Notes: 1. Accessories are field installed. For Factory installed items, see Made-to-Order Products on page 3.

LUMINAIRE DETAILS





Full cutoff design

Hinged housing for wiring, wattage and CCT select access




Photocell cover



Dark Sky Compatible*

Full Cutoff Wall Pack can be utilized in dark sky compliant plans when set to 3000K.

DIMENSIONS / DETAILS



Lumen Pkg.	a	b	c	weight
1	6.02"	9.84"	8.07"	5.07 lbs.
2	6.42"	12.83"	9.57"	7.05 lbs.

Factory settings:
5000K / Highest Wattage

PERFORMANCE / Data

Lumen Maintenance	
Ambient Temp.	TM-21 Lumen Maintenance (54,000 hours)
25° C (77° F)	87.80%
Ambient Temp.	TM-21 Theoretical L70 (hours)
25° C (77° F)	>54,000

Load Information	
Power Factor	≥0.9
THD	≤20%
Frequency	50/60 Hz
Operating Humidity	20% - 90% RH
Low Temp Start / Max Temp	-40° C (-40° F) / 50° C (122° F)

DISTRIBUTION

