



PRODUCT OVERVIEW

ETi SSL's VersaFloods include **3 Selectable Wattages X 3 Selectable CCTs X 2 Mounting Options**—It's like getting **18 lights in one!** Both the small and large VersaFlood series comes in various lumen package sizes. Equipped with 0-10V dimming, universal 120-277 voltage and 347-480V options, they are ideal for site lighting, building facades, small stadium lighting, accent lighting, flag poles, column and sign lighting, security and more.

M
MultiMount

3 Color
Preference®

3 LUMEN
BOOST®

5
YEAR
WARRANTY




INNOVATE. ILLUMINATE. INSPIRE.

Outdoor [Floods]

VERSAFLOOD SMALL

Scan code for more information



PERFORMANCE SUMMARY				
Lumen Packages	Lumen Pkg. Range (LB3)	Select. Watt. Levels	CCT (CP3)	Distribution
Lumen Pkg 1	2000	15	3000K 4000K 5000K	
Lumen Pkg 2	1900 – 4900	15 25 35	3000K 4000K 5000K	
Lumen Pkg 3	4500 – 8400	35 45 60	3000K 4000K 5000K	
Lumen Pkg 4	5900 – 11200	45 60 80	3000K 4000K 5000K	
Lumen Pkg 5	10500 – 16800	80 100 120	3000K 4000K 5000K	
Lumen Pkg 6	13000 – 21750	100 120 150	3000K 4000K 5000K	

Photocell with Enable/Disable Switch

Covered Access for CCT, Lumen Select, and Photo Cell Switches



*White available for Lumen Packages 1, 2 & 3 only

ELECTRICAL DATA

Operation: 120-277V 50/60Hz
 Low Temp Start / Max Temp: -30° C (-22 F) / 50° C= (122° F)
 Controls: 0-10V, Photocell Dusk-to-Dawn
 Surge Protection: 15-60W: 2.5kV, 80-150W: LIN-PE: 6.0kV, L-N: 4.0kV

CERTIFICATIONS & OTHER INFO

Warranty: 5 year
 Vibration Tested: 1.5G (Knuckle / Slipfitter), 3G (Trunnion)
 UL/cUL Listed: Wet location, IP65 Rated

TWO MOUNTING OPTIONS INCLUDED



Slipfit or Threaded Knuckle Mount (Pre-Installed)




Trunnion Mount

ACCESSORIES

Wall Mount Kit
 Junction Box Cover Kit
 Ground Spike Stake

VERSAFLOOD LARGE

PERFORMANCE SUMMARY				
Lumen Packages	Lumen Pkg. Range (LB3)	Selectable Watt. Levels	CCT (CP3)	Distribution
Lumen Pkg 1	16000 – 32000	100 150 205	3000K 4000K 5000K	
Lumen Pkg 2	24000 – 39000	150 200 255	3000K 4000K 5000K	
Lumen Pkg 3	39000 – 50000	250 290 330	3000K 4000K 5000K	

7-Pin Receptacle w/ Shorting Cap

Covered Access for CCT and Lumen Select Switches



ELECTRICAL DATA

Operation: 120-277V 50/60Hz, 347V 60Hz, 480V 60Hz
 Low Temp Start / Max Temp: -40° C (-40 F) / 50° C= (122° F)
 Controls: 0-10V, 7-Pin Receptacle w/ Shorting Cap
 Surge Protection: L/LIN-PE: 10kV, L-N: 6kV

CERTIFICATIONS & OTHER INFO

Warranty: 5 year
 Vibration Tested: 1.5G (Knuckle / Slipfitter), 3G (Trunnion)
 UL/cUL Listed: Wet location, IP65 Rated
 EPA: 1.4 ft² (lm pkg 1-2), 1.7 ft² (lm pkg 3)

Notes: 1. 347-480V Made to Order only. Lead times apply.

TWO MOUNTING OPTIONS INCLUDED



Slipfit Knuckle Mount (Pre-Installed)



Trunnion Mount

ACCESSORIES

7-Pin Receptacle Photocells
 Wire Guards

MADE TO ORDER

High Volt 347-480 options
 Surge Protection 10KVA (120-277V only)