



PRODUCT OVERVIEW


Each CLHB Compact High Bay luminaire combines a **small profile with superior lumen output**. This series contains 4 lumen packages, and each luminaire has 3 selectable wattages and 2 selectable CCTs. It also has an excellent operating temperature range from 22°F to 122°F.

With various made-to-order choices, including battery backup, high voltage and cord options, this series is ideal for garages, and workshops, or in a commercial setting in factories and warehouses.



INNOVATE. ILLUMINATE. INSPIRE.

COMPACT LINEAR HIGH BAY | 3 LUMEN BOOST® | 2 CCT COLOR PREFERENCE®

PERFORMANCE SUMMARY					Suspension Mount 3' Chain & V-Hooks Included
Lumen Packages	Lumen Pkg. Range (LB3)	Selectable Watt. Levels	CCT (CP2)	Dist. Plot	
Lumen Pkg. 1	8400 – 15800	60 80 110	4000K 5000K		
Lumen Pkg. 2	17000 – 23500	120 140 165	4000K 5000K		
Lumen Pkg. 3	25500 – 31500	180 200 220	4000K 5000K		
Lumen Pkg. 4	33500 – 43000	240 280 300	4000K 5000K		

* Lumen package ranges are approximate values.
For actual delivered lumen data please refer to spec sheet.

ELECTRICAL DATA

Operation: 120-277V 50/60Hz
Low Temp Start / Max Temp: -30°C (-22°F) / 50°C (122°F)
Controls: 0-10V, OC Sensor and BBU Options
Surge Protection: 6kV (10kVA MTO option available)

CERTIFICATIONS & OTHER INFO

Warranty: 5 year
DLC Premium
UL/cUL Listed: Damp, IP20 Rated



Lumen Pkg.
Sizes 1 & 2




Lumen Pkg.
Sizes 3 & 4

Sensor-ready Port
for plug-in Microwave
Sensor and PIR Sensor
Accessories




MOUNTING ACCESSORIES

(order separately)



Surface Mount Accessory



Pendant
Mounting Kit
Accessory

MTO OPTIONS

6', 14/3 So Cord w/ NEMA 125V or 277V Plug Options


10kVA Surge Protector

High Voltage, 347-480VAC

25W Battery Backup

WIRE GUARDS

(order separately)



Wire Guard for
Lumen Pkg. Sizes 3&4



Wire Guard for
Lumen Pkg. Sizes 1&2

OC SENSOR ACCESSORIES

(order separately)

Quick Install Microwave Sensor and PIR Sensor

Remote Control Occupancy Programmer